

CORTO		Front mowers		
		3200 F PROFIL	310 F	285 F

Mower				
Working width	m	3.05	3.05	2.82
Transport width	m	3.00	3.00	2.76
Swath width without swathing discs	mm, approx.	–	–	–
Swath width with 1 pair of swathing discs	mm, approx.	1100–1450	1100–1450	1000–1350
Swath width with 2 pairs of swathing discs	mm, approx.	900–1450	900–1450	800–1350
Mowing drums	Qty	4	4	4
Blades/drum	Qty	3	3	3
Regular cutting height	mm	42/30–52*	42	42
Cutting height with spacer ring (+6mm)	mm	48/–	48	48
Cutting height with high-cut bottom disc (+25mm)	mm	67/55–77*	67	67
Weight	kg, approx.	820/830*	750	700

Tractor requirements				
Hitch category	Cat.	II	II	II
PTO shaft speed	rpm	1000	540/1000	540/1000
Optional PTO shaft speed	rpm	–	750	750
Hydraulic spool valves		1 x sa ⁽¹⁾ /1 x da ⁽²⁾	1 x sa ⁽¹⁾	1 x sa ⁽¹⁾
Power requirement	kW/hp	51/70	51/70	45/60

Equipment				
Spring suspension		●	●	●
ACTIVE FLOAT		○	○	○
High-cut mowing disc		○	○	○
Spacer ring		○	○	○
Quick blade change		●	●	●
Without swathing discs		–	–	–
Swathing discs		●	●	●
Additional swathing discs		○	○	○
Hydraulic foldable protective covers		○	–	–
Hydraulic transport locking device		–	–	–
Hydraulic lift		–	–	–
Parking device/rollers		–	–	–
Warning signs with lighting		○	○	○
Double mirror		○	○	○

1 For ACTIVE FLOAT option

2 For hydraulic protective covers option

3 For hydraulic lift option

* Sub-type with infinitely variable height adjustment

● Standard ○ Optional □ Available – Not available

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer

CORTO		Rear mowers		
		3200 CONTOUR	220	190

Mower				
Working width	m	3.05	2.10	1.85
Transport width	m	2.05	1.95	1.80
Swath width without swathing discs	mm, approx.	2200	900	800
Swath width with 1 pair of swathing discs	mm, approx.	1100–1450	–	–
Swath width with 2 pairs of swathing discs	mm, approx.	900–1450	–	–
Mowing drums	Qty	4	2	2
Blades/drum	Qty	3	4	3
Regular cutting height	mm	42	42	42
Cutting height with spacer ring (+6mm)	mm	48	48	48
Cutting height with high-cut bottom disc (+25mm)	mm	67	67	67
Weight	kg, approx.	1050	590	540

Tractor requirements				
Hitch category	Cat.	II	II	II
PTO shaft speed	rpm	1000	540	540
Optional PTO shaft speed	rpm	–	–	–
Hydraulic spool valves		1 x sa ⁽¹⁾ /1 x da	1 x sa ⁽³⁾	1 x sa ⁽³⁾
Power requirement	kW/hp	51/70	33/45	29/39

Equipment				
Spring suspension		–	○	○
ACTIVE FLOAT		●	–	–
High-cut mowing disc		○	○	○
Spacer ring		○	○	○
Quick blade change		●	●	●
Without swathing discs		●	●	●
Swathing discs		○	–	–
Additional swathing discs		○	–	–
Hydraulic foldable protective covers		–	–	–
Hydraulic transport locking device		○	–	–
Hydraulic lift		–	○	○
Parking device/rollers		○/○	–	–
Warning signs with lighting		○	○	○
Double mirror		–	–	–

and their price list for local specification details. Some protective panels may have been removed to present the function more clearly in photographs. To avoid any risks, you should never remove these protective panels yourself. In this context, please refer to the relevant instructions in the operator's manual.